Technical Information



LOBA® ParkettCare



Product description

Ready to use acrylate dispersion. Protects finished parquet and hardwood floors through a care layer from minor scratches and wear marks. Increases the lifetime of the floor. Enhances old dulled floors optically and brings new shine on floors.

Range of Use

For the maintenance of finished hardwood floors optimally suited for all LOBADUR waterborne finishes. Also excellent adhesion on industrially UV-finished parquet floors.

Features

- Universal care product for all finished parquet and hardwood floors
- Excellent adhesion on critical surfaces like anti-scratch UV-finishes
- · Extends the lifetime of the finish
- · Brings new shine on old worn out floors

Technical Data

Article No. 10011 Application Rate approx. 3-4 l for 100 m² per application Package Size 10 l, 1 l Application Tool LOBATOOL Wischwiesel

Packing Pallet: 60 x 10 l

Box: 4 x 5 l
Pallet: 128 x 5 l
Box: 12 x 1 l

Drying Time

Can be carefully walked on after 1-2h
Fully stressable

After 12h

Pallet: 480 x 1 I

Storage and Pallet: 480 x 1 I

Thinner Do not dilute. Product is ready to use.

Contents (acc. to EU-recommendations): less the

+5°C to + 25°C (41°F to 77°F), Contents (acc. to EU-recommendations): less than 5% storable for 24 months, no nonionic surfactants, preservatives. Further

hazardous material according to ingredients: polymer dispersions, water-soluble ADR solvents

GISCODE GE 10 pH-value 8,4

Preparation:

Transportation

Floor must be free from dust and soilings. Remove loose dirt and dust in advance with a vacuum cleaner, brush or mop. Afterwards damp mop floor by using LOBA® CleanFix or LOBA® Cleaner. Residues of old careproducts must be entirely removed with LOBA® CareRemover. Therefor please also regard technical informations of the respective products.

Advices for engineered parquet floorings:

Due to the multidude of available engineered parquet types in combination with different finish qualities in this sector we also recommend to regard the Care instructions of the manufacturer. In case of doubt contact the manufacturer or the LOBA technical department. Alternatively the suitability of the product can be tested on a sample area.

Information on Use:

Shake material well. Apply ParkettCare equally on clean, dry floor with a LOBATOOL Wischwiesel (approx. 30-40 ml/m²). On larger areas a wide-headed wiper mop or another suitable applicator can be used alternatively. Put some of the material on the floor and apply in equally thick coats. Do not put any pressure on the applicator, leave the applicator on the floor during the application, do not lift. Start on one side of the room and work from wall to wall to the other side of the room in direction to the door. Do not process the floor during the drying phase, this could lead to streakings. The floor can be carefully walked on after 1-2h.

Basic Cleaning:

ParkettCare can be removed with LOBA® CareRemover, for details see technical information of the product.

The general information on the use of LOBACARE® products and our current care instructions are part of this information and must be noticed.